



**The Water Quality Indicator System  
with Accuracy, Alarm, Control,  
At The DI Tanks,  
OR, 700 feet Away!**

- ✓ Auto Temperature Compensation
- ✓ Built-In Alarm (non-alarm available)
- ✓ Steady Green/Flashing Red LEDs
- ✓ Output Port for Relay & Remote Alarm Modules
- ✓ 6 units per single transformer/outlet
- ✓ Safe 12 VDC
- ✓ Easy 1/2" or 3/4" installation
- ✓ 5 Set-points available



**Accuracy**


Auto Temperature Compensation (ATC) and Surface Mount Technology (SMT) electronics achieve  $\pm 3\%$  accuracy with  $\pm 1\%$  repeatability over a temperature span of 5 - 45°C (41 - 113°F).

**5 Set-Points**

Hy-Lites are available in 5 fixed set-points most popular for monitoring both two-bed and mixed-bed DI systems. Application can also include RO and Distillation:

- 25, 50, 200 kilohm-cm @ 25° C
- 1, 2, megohm-cm @ 25° C

**Unit-to-Unit Power**




Up to 6 Hy-Lites can be plugged into each other greatly reducing congestion at the wall outlet. The results are a more professional installation! Operational power is a safe 12 VDC supplied by a plug-in style transformer.

**Visual & Audible Alarm**

Easy to see Green and Red LEDs continuously display the status of pure water quality relative to set-point rating. Whenever the water is of acceptable purity, the Green light remains on. Should the purity fall below set-point, the Red light *Flashes* and the **built-in peizo Alarm** sounds! The alarm can be silenced by pressing the **membrane switch** in the front label, and will not resound until the next Red light condition occurs.

**Alarm / Display Modes**



**Versatile Insertion Cell**

The integral cell is designed for installation in standard threaded tees. 1/2" & 3/4" mNPT polypro fittings are provided. Cell construction is of trouble-free Stainless Steel electrodes and ABS.

**Control & Remote Alarm Capability**

Hy-Lites have an **Output Port** for connection to Relay and/or Remote Alarm Modules at distances up to **700 feet!** Telephone type cable/connectors result in fast and easy, *click-click*, installation.




The Remote Alarm Module has a peizo alarm, green/red LEDs, and silence switch to duplicate the operational status of the connected Hy-Lite. Both units act as a system, since silencing the alarm at either location will silence both alarms. The alarm module can also be ordered with an auto re-alarm feature.




The Relay Module allows the Hy-Lite to perform as a controller of valves, custom alarm systems, etc. A 1 amp SPDT relay features an adjustable time delay to compensate for expected equipment rinse-up times. There is also a signal pass-thru feature permitting the relay module to be used with the remote alarm module.

## Identification Drawing



## Module Configurations



## Specifications

**Accuracy:**  $\pm 3\%$  @ 5-45°C

**Repeatability:**  $\pm 1\%$

**Temperature Compensation:** Automatic to 25°C from 5-45°C (41-113°F)

**Available Set-Points:** (single fixed) 25, 50, 200 kilohm-cm @ 25°C  
1, 2 megohm-cm @ 25°C

**Visual Display:** Steady Green & Flashing Red LEDs

**Audible Alarm:** 70db peizo alarm with membrane overlay kill switch

**Circuitry:** Surface Mount Technology (SMT)

**Input Power:** 12VDC; 30 milliamps

**Transformer:** Plug-in, class 2, UL & CSA approved,  
Input 110 VAC, 50-60 Hz / Output 12 VDC @ 200 mA  
integral 6' cable

**Patchcord:** 8' with male termination's

**Output to Module Connection:** 4 wire, 26 ga, UL4110 telephone cable  
with FCC modular handset connectors

**Materials of Construction:**

Wetted: 303 SS, ABS, Polypropylene, Viton

Non-Wetted: enclosure/ABS ; labels/polyester, chrome-mylar

**Operating Pressure:** 0 - 150psi

**Fittings:** 1/2" or 3/4" mNPT

**Dimensions:** overall length - 6"...enclosure length - 3"... width - 2"  
overall height w/LED's - 2"

## Ordering Information

**Model:**      **Description:**

**HLA**      **Hy-Lite with Alarm & Output Port**

-25, -50, or -200 kilohm-cm  
-1, or -2 megohm-cm

**HLS**      **Silent Hy-Lite with Output Port**

-25, -50, or -200 kilohm-cm  
-1, or -2 megohm-cm

**RMA**      **Remote Alarm Module**

**RMR**      **Relay Module**

**RMAR**      **Remote Alarm Module with Re-Alarm**

Note: Transformers and Patchcords Ordered Separately

**Accessories:**

**HyTran-A,**

Plug-in 110 VAC/12 VDC Transformer  
with 8' output cord

**HyTran-B, Euro**

Plug-in 230VAC/50Hz/12VDC *Euro-style* plug  
\*contact factory for other power configurations

**HyPC,**

Hy-Lite to Hy-Lite Patchcord, 8'

**RPC,**

Hy-Lite to Remote Module Cables,  
-10, -50, -100, -200 ft, custom lengths

## Hydro-Check Systems, Inc

5931 Sea Lion Place, Suite 100, Carlsbad, CA, USA, 92008  
tel 760-930-1924      760-930-1934 fax  
[www.hydrocheck.com](http://www.hydrocheck.com)

The **Hydro-Check Systems Hy-Lite, Modules, and accessories** have a warranty against defects in materials and workmanship for a period of 2 years from the date of manufacture. Warranty items returned prepaid will be repaired or replaced by the factory at no charge. Warranty applies only to product defects and **Hydro-Check Systems** accepts no other liability.